

Dewalt DCN692P2-XE - 18V Brushless 2 Speed Framing Nailer Kit (2 x 5.0Ah)



Product Description

Includes

- DCN692P2 - 90mm Framing Nailer
- 2 x 18V 5.0Ah XR Li-Ion battery packs with state of charge indicator
- Multi-voltage XR charger
- Reversible belt hook
- Non-mar tip
- Heavy duty carrying case

Features

- 18V XR Li-Ion Two Speed Framing Nailer featuring BRUSHLESS motor technology and XR 5.0Ah battery packs
- Two speeds - or power levels - to optimise the nailer for firing all lengths of nails
- Benefit from longer runtime, quicker readiness to fire, less recoil and more durability when firing short nails
- BRUSHLESS motor technology offers the power to fire a 90mm Ring Shank nail in Soft Wood and 63mm into Hard Woods
- The sequential operating mode allows for precision placement and the bump operating mode provides the user with production speed
- High capacity 5.0Ah XR battery packs offer eXtreme Runtime in both speeds and versatility to share power with your other 18V XR power tools
- Mechanical rather than gas operation offers constant performance at temperature between -20 and 50 degrees celcius and minimal cleaning/service requirements
- Class leading vibration and sound figures, offer fantastic user protection
- Versatile 30 - 34 degree magazine angle will accept most clipped head, and off centre round head paper tape or wire weld collated framing nails
- Reversible belt/rafter hook provides increased portability and versatility on the job-site
- Depths can be easily adjusted using the thumb wheel depth adjuster
- Increased visibility and durability along with protection for work-surface from the non-mar contact-trip
- Ergonomic tool design allows the nailer to fit easily between a 400mm centre stud
- Gas free operation offers a significant saving in running costs
- Tool free stall/jam clearance minimises user down time
- Cordless design allows you to work without the inconvenience and safety risk of trailing leads
- User can engage contact trip lock-off and prevent accidental dis-charge of fastener
- Dry fire lockout ensures that the tool is protected from firing without nails in the magazine

Specifications

- Nail Diameter: 2.8 - 3.3 mm
- Battery Capacity: 5.0 Ah
- Magazine angle: 30 - 34 °
- Nail Length: 50 - 90 mm
- Magazine capacity: Up to 55 Nails
- Magazine loading: Rear - load
- Firing mode: Bump & Sequential
- Length: 345 mm
- Width: 125 mm

- Height: 338 mm
- Weight: 4.1 kg
- Voltage: 18 V
- Nailer Operating Mode: Selective
- Integrated Belt Hook: Yes
- Jam Clearing: Yes
- Impact energy (EPTA 05/2009): 105 J
- Temperature Range: -20 to 50°C
- Fault indicator: Yes
- Battery chemistry: XR Li-Ion