

## Metabo WEV15125Q - Angle Grinder 125mm 1550W Quick Nut Safety Clutch Soft Start Constant Torque Variable Speed



### Product Description

---

#### Features

- Highest service life for extreme applications: robust, powerful angle grinder with speed control and greatest power density in its class for quick work progress
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

#### Specifications

- Grinding wheel Ø: 125 mm / 5 "
- Rated input power: 1550 W
- Output power: 940 W
- No-load speed: 2800 - 11000 rpm
- Revolutions at rated load: 11000 rpm
- Torque: 3.5 Nm / 31 in-lbs
- Spindle thread: M 14
- Weight (without power cable): 2.5 kg / 5.5 lbs
- Cable length: 4 m / 13 ft
- Vibration
  - Surface grinding: 6 m/s<sup>2</sup>
  - Uncertainty of measurement K: 1.5 m/s<sup>2</sup>
  - Grinding with sandpaper: 3.6 m/s<sup>2</sup>
  - Uncertainty of measurement K: 1.5 m/s<sup>2</sup>
- Noise emission
  - Sound pressure level: 93 dB(A)
  - Sound power level (LwA): 104 dB(A)
  - Uncertainty of measurement K: 3 dB(A)

#### Includes

- Guard
- Inner support flange

- M-Quick flange nut
- Metabo VibraTech (MVT) side handle