

## Metabo MT18LTXSK - 18V Multi Tool (Tool Only)



### Product Description

---

#### Features

- Oscillating cordless multi-tool with high performance comparable to that of a mains powered version
- Indispensable for interior development such as cutting, sanding and scraping of different materials
- Tool holder for maximum compatibility to OIS, Starlock and other accessories
- Metabo Quick tool change system for time-saving, convenient change of accessories
- Fast and powerful thanks to the combination of a large oscillation angle of 3.2° and VTC-Electronics to maintain constant speed even under load
- Extra bright double LED lights for good visibility of the working area
- Slim design and non-slip soft-grip surface for optimised handling
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

#### Specifications

- Battery pack voltage: 18 V
- Orbital frequency with no load: 7000 - 18000 rpm
- Oscillation angle left/right 1.6 °
- Bit retainer: Compatible with OIS and Starlock
- Base plate, dimensions from corner to corner: 93 mm / 3 5/8 "
- Weight (including battery pack): 1.8 kg / 4 lbs
- Vibration
  - Surface grinding: 7.5 m/s<sup>2</sup>
  - Uncertainty of measurement K: 1.5 m/s<sup>2</sup>
  - Scraping: 11.5 m/s<sup>2</sup>
  - Uncertainty of measurement K: 1.5 m/s<sup>2</sup>
  - Sawing with plunge cut saw blade: 13 m/s<sup>2</sup>
  - Sawing with segmented sawing blade: 11.6 m/s<sup>2</sup>
  - Uncertainty of measurement K: 3 m/s<sup>2</sup>
- Noise emission
  - Sound pressure level: 77 dB(A)
  - Sound power level (LwA): 88 dB(A)
  - Uncertainty of measurement K: 3 dB(A)

#### Includes

- Plunge saw blade 32 mm HCS (wood)
- Triangular hook and loop sanding plate 93 mm
- 5 Hook and loop sanding sheets 93 mm P 80
- 5 Hook and loop sanding sheets 93 mm P 120
- Suction Adapter
- Multi-adapter
- MetaLoc case insert