

Dewalt DCF620P2K-XE - 18V Brushless Collated Screwgun Kit (2 x 5.0Ah)



Product Description

Includes

- DCF620 - Collated Screwgun
- 2 x 18V 5.0Ah batteries
- Charger
- DCF6201 - collated screw magazine
- DT7205-QZ - PR2 collated screw bit
- Single Screw Nose cone
- DT7520-QZ - Magnetic bit extender with 25mm PR2 screw bit
- TSTAK 2 Kitbox

Features

- 18V XR Li-Ion BRUSHLESS Drywall Screwdriver for efficient fitting of drywall
- Powerful 4400rpm BRUSHLESS motor drives screws efficiently and effectively offering maximum runtime and a compact tool
- One of the lightest and most compact tools on the market - it ensures that you can work comfortably and get into small spaces
- Quick release collated screw magazine accepts most collated screws to allow the user to fit boards more quickly
- Easy collated screw magazine opening to allow for quick cleaning of drywall dust
- Tool free depth control and fine depth control for simple but effective setting
- Collated screw magazine rotates on tool without removal to allow the operate in corners with the minimum of fuss
- LED worklight offers valuable light when working in small spaces or areas with limited light
- 5.0Ah High Capacity battery pack coupled with the BRUSHLESS motor offers eXtreme Runtime and compatability with the rest of your 18V XR tools
- Trigger lock on lets you work without having to pull the trigger
- Ergonomically designed rubber grip gives you excellent user comfort whilst using the tool in either the "in-line" or "pistol-grip" hand position
- Also supplied with locking nose cone so that you can work with the same tool on sites where collated drywall screws are not supplied
- "Set and forget" feature remembers your fine depth adjustment setting when removing and replacing the nose cone
- Robust and durable design means that the tool is jobsite tough
- Angled belt hook can be positioned for left or right handed users and fixes tool strongly onto tool belt / pouch
- Supplied with TSTAK 2 kitbox to interconnect with all of the rest of your TSTAK storage system

Specifications

- Voltage: 18 V
- Battery Capacity: 5.0 Ah
- Tool Holder (Hex): 6.35 mm
- Power Output: 435 Watts
- No Load Speed: 0 - 4400 rpm
- Max Torque: 5 - 30 Nm
- Weight: 1.88 kg
- Length: 380 mm
- Height: 233 mm
- Hand/Arm Vibration: <2.5 m/s²

- Uncertainty K 1 (Vibration): 1.5 m/s²
- Sound Pressure: 77 dB(A)
- Uncertainty K 1 (Sound): 3 dB(A)
- Accoustic Pressure: 88 dB(A)
- Uncertainty K 2 (Sound): 3 dB(A)
- Battery chemistry: Li-Ion
- Head Length: 335 mm