

Metabo LSV5-225 COMFORT - Drywall Sander 500W 225mm Variable Speed 1000-1650RPM Adjust Length 1.1 / 1.6 / 2.1 m



Product Description

Features

- For convenient sanding of primed surfaces on walls or ceilings
- Selectable LED side light to help detect imperfections and serrations and ensure a perfect finish.
- Optimum balance when working, as the centre of gravity of the machine is not at the sanding head
- Variable length adjustment: can be shortened or extended without tools for narrow rooms or high ceiling rooms
- Extendable to a total length of 2.1 m with additional extension (accessory)
- M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head
- Sanding near edges, corners and adjoining sections time-saving and effective
- Ideal adaptation of the flexible sanding head to the surface for good work results
- Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface.
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions
- Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed
- $\bullet\,$ Putting the machine down without kinking the hose and cable
- With extensive range of grinding media for every application
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

Specifications

- Sanding disc diameter: 225 mm / 8 7/8 "
- No-load speed: 1000 1650 rpm
- Rated input power: 500 W
- Output power: 270 W
- Adjustable machine length: 1.1 / 1.6 / 2.1 m // 41 3/8 / 61 7/32 / 81 1/16 "
- Weight (without power cable): 4.5 kg / 9.9 lbs
- Cable length: 4 m / 157 1/2 "
- Vibration
 - O Surface grinding: 2.5 m/s²
 - O Uncertainty of measurement K: 1.5 m/s²
- Noise emission
 - o Sound pressure level: 76 dB(A)
 - O Sound power level (LwA): 87 dB(A)
 - O Uncertainty of measurement K: 3 dB(A)

Includes

- Sanding pad (very soft)
- Hook and loop sanding sheets with multi-perforation (1 each of P80, P100, P120, P150)
- Flexible shaft (as replacement)
- Coupling bush

- Extension
- Hexagonal wrench
- Plastic carry case