

Metabo WEF15125Q - Angle Grinder 125mm Flathead 1500W



Product Description

Features

- Powerful flat-head angle grinder for working quickly in acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT) side handle for vibration damping to protect the user's health
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Specifications

- Minimum accessible angle: 43 °
- Grinding wheel Ø: 125 mm / 5 "
- Rated input power: 1550 W
- Output power: 940 W
- No-load speed: 11000 rpm
- Revolutions at rated load: 11000 rpm
- Torque: 3.5 Nm / 31 in-lbs
- Spindle thread: M 14
- Weight (without power cable): 2.7 kg / 5.9 lbs
- Cable length: 4 m / 13 ft
- Vibration
 - Surface grinding: 6 m/s²
 - $\circ~$ Uncertainty of measurement K: 1.5 m/s^2
 - $\circ~$ Grinding with sandpaper: 3.6 m/s^2
 - $\,\circ\,$ Uncertainty of measurement K: 1.5 m/s²
- Noise emission
 - $\circ~$ Sound pressure level: 91 dB(A)
 - Sound power level (LwA): 102 dB(A)
 - Uncertainty of measurement K: 3 dB(A)

Includes

- Guard
- Inner support flange
- Quick-locking nut
- Metabo VibraTech (MVT) side handle
- 1 Flap disc Flexiamant Super Convex (125mm; P60)

• 1 Roughing disc Flexiamant Super FKS 60 (125x4mm; P60)