

Dewalt DCH333NT-XJ - 54V Flexvolt Brushless 3-Mode SDS+ Rotary Hammer (Tool Only)



Product Description

Features

- Category-leading high speed drilling performance at more than 66 holes (18mm Ø x 80mm) per charge
- Rotation stop mode for light chiselling in plaster, tiles and render and impact stop mode for rotary only drilling in wood and metal
- Brushless motor with high capacity XR FLEXVOLT 9.0Ah 18V/54V Lithium-ion battery (not included) platform for extreme runtime and reduced maintenance
- Perform & Protect: best-in-class vibration at 8.5m/s², minimising user fatigue
- Bright white LED with delay feature improves visibility
- Ideal for drilling anchors and fixing holes into concrete, brick and masonry from 4mm to 30mm
- Compact, lightweight and ergonomic design for improved comfort and support during extended operating periods

Specifications

- Impact energy (EPTA 05/2009): 3.5 J
- No Load Speed: 0-1000 rpm
- Blows per Minute: 0-4480 bpm
- Max. Drilling Capacity [Concrete]: 30 mm
- Max. Drilling Capacity [Wood]: 30 mm
- Max. Drilling Capacity [Metal]: 13 mm
- Weight: 3.7 kg
- Weight (incl. battery): 4,950 g
- Length: 400 mm
- Height: 250 mm
- Width: 95 mm
- Hand/Arm Vibration - Hammer drilling into concrete: 7.5 m/s²
- Uncertainty K 1 (Vibration): 1.5 m/s²
- Hand/Arm Vibration - Chiselling: 8.5 m/s²
- Uncertainty K 2 (Vibration): 1.5 m/s²
- Hand/Arm Vibration - Drilling into metal: <2.5 m/s²
- Uncertainty K 3 (Vibration): 1.5 m/s²
- Hand/Arm Vibration - Screw driving without impact: <2.5 m/s²
- Uncertainty K 4 (Vibration): 1.5 m/s²
- Sound Pressure: 94 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 105 dB(A)
- Sound Power Uncertainty: 3 dB(A)

Includes

- Belt hook
- Multi-position side handle
- Heavy duty kit box