

## Husqvarna 525BX - Commercial Blower 25.4CC 525BX



## **Product Description**

A powerful and well-balanced handheld Husqvarna blower for professional use. The patented X-torq engine technology in combination with the special fan and housing design means high blowing capacity that is easy to control. The 525BX commercial leaf blower features an anti-vibration system 'Low Vib' making work less strenuous – even during long shifts. And all intuitive controls, i.e. Cruise Control, contribute to efficient and convenient operation at all times.

## Features

- X-Torq @ engine The X-Torq ® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.
- Adjustable tube length The blowing tube length is adjustable for best performance.
- Auto return stop switch Stop switch automatically resets to the ON position for trouble-free starting.
- Cruise control Fan speed can be set for easier handling.
- In line outlet The fan housing is designed so that the air stream is in line with the handle. This makes the machine very easy to manoeuvre.

## Specifications

- Engine
  - Cylinder displacement: 25.4 cm<sup>3</sup>
  - Power output: 0.85 kW
  - Maximum power speed: 7300 rpm
  - Fuel tank volume: 0.45 l
  - Fuel consumption: 518 g/kWh
  - Spark plug: NGK BPMR8Y
  - Idling speed: 3000 rpm
  - Electrode gap: 0.65 mm
- Dimensions
  - Weight: 4.3 kg
  - Tube diameter: 68 mm
  - Tube length: 550 mm
- Sound and Noise
  - Sound power level, guaranteed (LWA): 106 dB(A)
  - $\circ~$  Sound power level, measured: 104 dB(A) ~
  - $\,\circ\,$  Sound pressure level at operators ear: 91 dB(A)
- Capacity
  - $\circ~$  Air flow in housing: 14 m³/min
  - Air flow in pipe: 13 m³/min
  - $\circ$  Air speed (flat nozzle): 86 m/s
  - $\circ$  Air speed (round nozzle): 70 m/s
- Equipment
  - Tube length: 550 mm
- Vibration
  - $\circ~$  Equivalent vibration level (ahv, eq) handle: 1.2  $m/s^2$