

Metabo SBEV10002 - Hammer Drill 1000W 13mm Chuck Safety Clutch Vari 2 Speed 1000/2800RPM Const Torque Soft Start



Product Description

Features

- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for Speed Preselection
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Metabo Marathon-motor with dust protection for long service life
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Restart protection: prevents unintentional start-up after power supply interruption
- Cable-protecting ball joint for optimal freedom of motion when working

Specifications

- Rated Input Power: 1010W
- Output Power: 540W
- Maximum Torque: 40 / 14Nm // 354 / 124in-lbs
- Drill-Ø Masonry: 22mm / 7/8"
- Drill-Ø Concrete: 20mm / 25/32"
- Drill Ø Steel: 16 / 10mm // 5/8 / 3/8"
- Drill-Ø Soft Wood: 40 / 25mm // 1-9/16 / 1"
- No-Load Speed: 0 - 1000 / 0 - 2800rpm
- Revolutions at Rated Load: 1000 / 2800rpm
- Maximum Impact Rate: 53200bpm
- Gears: 2
- Chuck Capacity: 1.5 - 13mm // 1/16 - 1/2"
- Collar Diameter: 43mm / 1-11/16"
- Drill Spindle with Hexagonal Recess: 6.35mm / 1/4"
- Drill Spindle Thread: 1/2" - 20UNF
- Chuck Clamping Type: Keyless Chuck
- Weight (without power cable): 2.7kg / 6lbs
- Cable Length: 4m / 13ft