

Alemlube SO600 - Oxy Acet Hose Reel 6x15mm



Product Description

Oxy-Acetylene Steel Reel - 6mm x 15m

- The new SO600 Oxy Acetylene & Oxy/LPG hose reel from Alemlube is a genuine industrial quality welding reel ideal for all general welding applications undertaken by contractors, fabricators and people involved in the construction and industrial fields. Featuring impact resistant UV stabilised covers for maximum durability and an automatic and positive latching mechanism, the SO600 can easily be mounted on the wall or ceiling and can be carried in utes and service vehicles.
- The heavy duty spring assembly retrieves the rubber hose even when fully extended and the tension adjustability function enables the spring tension to be adjusted to suit each individual application. The SO600 Oxy Acetylene hose reel from Alemlube has a maximum working pressure of 300psi, dimensions of 630 x 442 x 261mm and helps to comply with increasing OH&S requirements enabling you to provide a safer working environment while at the same time increasing efficiency and productivity.
- Impact resistant UV stabilised covers for maximum durability
- Can be mounted on the wall or ceiling
- Automatic and positive latching mechanism
- 5/8" BSPT inlet/outlet
- Ideal for back of UTE or service vehicle mobile use
- Adjustable spring tension & high flow swivel and fluid path
- Detachable steel mounting bracket enables 180° hose reel rotation
- 15m x 6mm ID hose & 0.9m lead in hose