

Dewalt D25733K-XE - Rotary Hammer 1600W 48mm SDS Max 13.3J



Product Description

Features

- Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 125 mm
- Active vibration control system incorporating a counterbalance mass and floating handle delivers extremely low vibration
- An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power
- Electronic speed and impact energy control
- Lock-on switch for chipping
- Rotation-stop for demolition applications in brick, masonry and light chasing in concrete
- Brush wear and service indicators

Specifications

- Tool Holder: SDS-Max
- Power Input: 1600 Watts
- Impact energy (EPTA 05/2009): 13.3 J
- Load Speed: 177-355 rpm
- Blows per Minute: 1350-2705 bpm
- Max. Drilling Capacity [Concrete]: 48 mm
- Max. Drilling Capacity [Breakthrough bit]: 80 mm
- Max. Drilling Capacity [Core bit]: 125 mm
- Weight: 9.3 kg
- Length: 544 mm
- Height: 292 mm
- Width: 115 mm
- Hand/Arm Vibration - Hammer drilling into concrete: 9.6 m/s²
- Uncertainty K 1 (Vibration): 1.5 m/s²
- Hand/Arm Vibration - Chiselling: 9.0 m/s²
- Uncertainty K 2 (Vibration): 1.5 m/s²
- Sound Pressure: 0 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 0 dB(A)
- Sound Power Uncertainty: 4 dB(A)