

Metabo SB18LTX3BLI40K - 18V Brushless Hammer Drill Driver Kit (2 x 4.0Ah)



Product Description

Includes

- SB18LTX3BLI- 18V Brushless Hammer Drill Driver
- 2 x 18V 4.0Ah Batteries
- Fast Charger
- Metlock Case
- Futuro Plus keyless chuck with metal sleeve
- without battery pack, without charger
- Side handle
- Belt hook and bit case

Features

- Brushless 3-speed hammer drill with maximum power for demanding applications
- Third speed setting with high torque (max. 3800/min) for extended range of application and even faster drilling progress
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- High-performance impact mechanism for optimum drilling performance
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- With handy belt hook and bit case which can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Specifications

- Battery pack voltage: 18 V
- Maximum torque - soft: 60 Nm / 531 in-lbs
- Pulse torque: 65 Nm / 48 in-lbs
- Maximum torque, hard: 120 Nm / 1062 in-lbs
- Adjustable torque: 1 - 20 Nm // 9 - 177 in-lbs
- Drill-Ø masonry: 16 mm / 5/8 "
- Drill-Ø concrete: 16 mm / 5/8 "
- Drill Ø steel: 13 mm / 1/2 "
- Drill-Ø soft wood: 65 mm / 2 1/2 "
- No-load speed: 0 - 500 / 0 - 2050 / 0 - 3800 rpm
- Maximum impact rate: 32300 bpm
- Chuck capacity: 1.5 - 13 mm // 1/16 - 1/2 "
- Weight (including battery pack): 2.3 kg
- Vibration
 - Drilling in metal: 3.8 m/s²

- Uncertainty of measurement K: 1.5 m/s²
 - Impact drilling concrete: 17.7 m/s²
 - Uncertainty of measurement K: 1.5 m/s²
- Noise emission
 - Sound pressure level: 71 dB(A)
 - Sound power level (L_{WA}): 82 dB(A)
 - Uncertainty of measurement K: 3 dB(A)