


## Beaver 500103M - Chain Block - 1 Tonne 3m Drop



### Product Description

Chain blocks are designed for use on monorails, jibs & fixed installations and for maintenance use. They are to be used for vertical lifts only as if they are side loaded or used horizontally, jamming of the loader chain and damage to the blocks may occur.

- Beaver 3G industrial chain blocks are colour coded to match international lifting standards for fast and accurate identification of W.L.L.
- The Beaver 3G Industrial Chain Block has improved reinforced side covers, made from heavy duty steel to ensure full protection of the vital gears, shafts and bearings.
- The load chain is made of high resistance, Grade 80 Alloy Steel, black finish, heat treated, calibrated and marked according to Australian standard of AS1418.2.
- All Beaver chain block gears are fitted with industrial Roller bearings.
- Strong and engineering designed gear on Ratchet gear part to ensure maximum performance and security.
- Machined and heat treated gears, offering better durability and longer life cycle.
- Superior Weston type friction braking system that works with load pressure and incorporates high strength twin synchronized pawls for additional safety ensuring that it couldn't be free wheeled, extending the product life.
- The top and bottom hooks come with cast/heavy duty latches.
- Top and bottom hooks fitted with ball bearings to allow rotation under load.
- Every Beaver 3G Industrial Chain Block is operationally tested to its rated capacity and is supplied with a Beaver test certificate, relating to its stamped identification side plate.
- Beaver 'ID' plates and rivets are supplied in stainless steel and non conductive material in order to avoid dangerous sparking, making them ideal for underground mining.
- A comprehensive range of spare parts are available, complete with full repair facilities and re-testing to NATA specifications.
- Rated Capacity: 1000kg
- Colour Code: Violet
- Standard Lift: 3m
- Falls of Chain: 1
- Efforts to lift full load: 33kg
- Net Weight: 11kg
- Hand chain overhauled to lift load one metre: 39mm
- Load chain diameter: 6mm
- Dimensions
  - A (Headroom): 340mm
  - B (Width): 170mm
  - C (Depth): 135mm
  - D (Diameter): 150mm
  - Hook opening (upper): 28mm
  - Hook opening (lower): 28mm