

## Makita DK0114G209 - 40V Max Brushless 2 Piece Drill/Driver Combo Kit (2 x 4.0Ah)



### Product Description

---

#### Includes

- HP001GZ - 40V Max Brushless Hammer Driver Drill
- TD001GZ - 40V Max Brushless Impact Driver
- BL4040 x2 - 40V Max 4.0Ah Battery
- DC40RA - 40V Max Single Port Rapid Charger
- 832319-7 - Tote Bag

#### HP001GZ - 40V Max Brushless Hammer Driver Drill

- Heavy duty power with 141Nm peak torque
- Active feedback sensors shut down the tool in the event of a kickback
- Massive drilling capacity with 152mm hole saw & 50mm auger bit capacity
- 35% faster drilling speed compared with the equivalent 18V model
- Electronic clutch for selecting between 41 torque range settings
- Impact Rate: Hi: 0 - 39,000ipm / Lo: 0 - 9,750ipm
- Max. drilling capacities in masonry: 20mm
- Max. drilling capacities in steel: 20mm
- Max. drilling capacities in wood: Auger bit: 50mm, Self-feeding bit: 76mm, Hole saw: 152mm
- Max. lock torque: 125Nm
- Max. peak torque: 141Nm
- Max. tightening torque: Hard: 140Nm / Soft: 68Nm
- No Load Speed: Hi: 0 - 2,600rpm / Lo: 0 - 650rpm
- Overall Length: 182mm
- Skin weight: 2.0kg
- Voltage: 40V Max
- Weight (with battery): 3.0kg (BL4040)
- Includes
  - Grip assembly (127551-9)
  - Belt hook assembly (346317-0 & 251314-2)
  - +- BIT 2-45 (784637-8)
  - Bit holder (452947-8)
  - Stopper pole assembly (122576-8)

#### TD001GZ - 40V Max Brushless Impact Driver

- Heavy duty power with 220Nm max. torque
- Precision fastening with enhanced anvil stability for less bit wobble
- Optimised application selector with 6 modes adapting speed and impacts for each task
- Single hand quick change trigger allows user to change between speeds and modes at the touch of a button
- Constant speed control allows tool to operate at the same speed regardless of battery capacity
- Drive Shank: 6.35mm (1/4") Hex

- Impact Rate: Max.: 0 - 4,400ipm / Hard: 0 - 3,600ipm / Med: 0 - 2,600ipm / Soft: 0 - 1,100ipm
- Max. capacities high tensile bolt: M5 - M14
- Max. capacities standard bolt: M5 - M16
- Max. tightening torque: Max.: 220Nm / Hard: 170Nm / Med: 50Nm / Soft: 20Nm
- No Load Speed: Max.: 0 - 3,700rpm / Hard: 0 - 3,200rpm / Med: 0 - 2,100rpm / Soft: 0 - 1,100rpm
- Overall Length: 120mm
- Skin weight: 1.0kg
- Voltage: 40V Max
- Weight (with battery): 1.7kg (BL4025)