

## Milwaukee M12FRAIWF38-0 - 12V Brushless 3/8" (Friction Ring) Right Angle Impact Wrench (Tool Only)



## **Product Description**

The M12 FUEL™ 3/8" Right Angle Impact Wrench with Friction Ring is a powerful right angle impact wrench. User's will be able to easily remove stubborn bolts and fasteners with up to 300 Nm of nut-busting torque. This cordless right angle impact wrench also gives user's maximum access with ultimate control in hard to reach applications. The durable cordless impact wrench easily fits into tight spaces with a profile head of only 56 mm. This allows users to be more productive by decreasing the need for socket extensions often used with pistol-grip impact tools. The 4-Mode DRIVE CONTROL delivers unmatched control in various fastening and bolt removal applications. Modes 1-3 provide RPM and IPM adjustments for maximum precision, while Mode 4 is equipped with Auto Shut-Off in forward and Bolt Removal Mode in reverse. Auto Shut-Off Mode will prevent over-tightening of bolts by applying no more than 20 Nm of torque. Bolt Removal Mode provides more control by drastically slowing down RPMs once the bolt is loosened. The REDLINK PLUS™ Intelligence ensures maximum performance and protection against overloads, over-heating, and over-discharge. This cordless 3/8" Impact Wrench is powered by MILWAUKEE® M12™ REDLITHIUM™-ION Battery Packs (not included), which are compatible with all M12™ tools, delivering more work per charge and more work over the life of the pack.

## Features

- POWERSTATE™ Brushless Motor delivers the power to complete a wide variety of applications
- Powerful right angle impact wrench with up to 300 Nm nut-busting torque
- 358mm body (with M12B3) and 56 mm head profile allow for more access in tight, hard to reach spaces
- Auto Shut-Off mode prevents over tightening and increases productivity by applying no more than 20Nm of torque
- Bolt removal mode offers more control after bolt breakaway as RPMs drastically slow down once the bolt is loosened
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- Works in up to to 69kV environments
- REDLINK PLUS™ Intelligence ensures maximum performance and protects from overloads, heating and over-discharge

## **Specifications**

ANVIL TYPE: 3/8" Square w/ Friction Ring
IPM: 0-1,350 / 0-2,700 / 0-3,600 / 0-3,600

WARRANTY: 5 Years

• WEIGHT: 1.27 kg (Tool only)

• DRIVE CONTROL: 4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode

NUT BUSTING TORQUE: 300 NmFASTENING TORQUE: 270 Nm

• LENGTH: 338mm

• RPM: 0-1,550 / 0-2,300 / 0-3,000 / 0-3,000

PLATFORM: M12 FUEL™