

Metabo TS254MSET - Table Saw 1500W 254mm C/W Stand



Product Description

TS 254 M Table Saw (910254190) + TSU Table Saw Stand (629003000)

Features

- Compact mobile table saw with impressive cutting performance and high comfort for working
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precisely adjustable rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 - 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces

Specifications

- Dimensions: 669 x 748 x 334 mm // 26.343 x 29.437 x 13.156 "
- Working height: 334 mm // 13.15 "
- Cutting height: 0 - 80 mm // 0 - 3.15 "
- Maximum cutting height 90/45°: 80 / 48 mm // 3.15 / 1.87 "
- Maximum cutting width at rip fence: 520 mm / 20.46 "
- Maximum material width at mitre fence: 195 mm / 7.68 "
- No-load speed: 4200 rpm
- Cutting speed: 56 m/s / 184 ft/s
- Saw blade: 254 x 30 mm // 10 x 1.181 "
- Saw blade swivel range: -1.5 - 46.5 °
- Rated input power S1 100%: 1500 W
- Weight: 24.4 kg / 54 lbs
- Noise emission
 - Sound pressure level: 92 dB(A)
 - Sound power level (LwA): 105 dB(A)
 - Uncertainty of measurement K: 3 dB(A)

Includes

- Carbide saw blade with alternately bevel-ground tips (40 teeth)
- Table Length Extension
- Table width extension (right)
- Push stick
- Rip Fence

- Mitre Fence
- 629003000 - TSU Table Saw Stand
 - For ideal working height and stability
 - Foldable
 - Weight: 5.9 kg
 - Max. load with attached machine: 125 kg (machine + work-piece)