

Milwaukee M18FIW2F12-502C - 18V Brushless 1/2" (Friction Ring) Compact Impact

Wrench Kit $(2 \times 5.0Ah)$



Product Description

The M18 FUEL[™] 1/2" Compact Impact Wrench with Friction Ring delivers maximum access in tight spaces, up to 339 Nm of nut-busting torque, and maximum workspace visibility. This battery-powered impact wrench measures only 124.5 mm in length, with a POWERSTATE[™] Brushless Motor to provide the power to remove stubborn fasteners, even in confined spaces. The MILWAUKEE® 1/2" Compact Impact Wrench with Friction Ring has tri-LEDs that surround the anvil to deliver the user brighter light with fewer shadows. 4-Mode DRIVE CONTROL offers enhanced precision with a range of pre-set RPM and IPM levels, selectable from a single button on the tool. By selecting Mode 4, Auto Shut-Off Mode applies no more than 27 Nm of torque for hand-tight fastening applications to prevent overtightening. Mode 4 also features Bolt Removal Mode, where the tool delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops. REDLINK[™] PLUS Intelligence electronics make these controls possible while ensuring maximum performance, protecting the tool against overloads, overheating, and over-discharge. The M18[™] REDLITHIUM[™]-ION battery pack (not included) fits all M18[™] tools, delivering more work per charge and more work over the life of the pack.

Includes

- (1) M18 FUEL[™] 1/2" Compact Impact Wrench with Friction Ring (M18FIW2F12-0)
- (2) M18[™] 5.0Ah REDLITHIUM[™]-ION Battery (M18B5)
- (1) M12[™] & M18[™] Rapid Charger (M12-18FC)
- (1) Belt Clip
- (1) Carrying Case

Features

- Friction ring ensures quick and easy socket changes
- POWERSTATE™ Brushless Motor delivers up to 339 Nm of nut-busting torque
- 4-Mode DRIVE CONTROL provides control over output speed and power
- Auto Shut-Off Mode prevents over tightening and increases productivity by applying no more than 27 Nm of torque
- Bolt Removal Mode delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- 124.5 mm in length for maximum access in tight spaces
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- Works in up to 69kV environments
- REDLINK™ PLUS Intelligence ensures maximum performance and protects from overloads, heating and over-discharge

Specifications

- PLATFORM: M18 FUEL™
- ANVIL TYPE: 1/2" Square with Friction Ring
- NUT BUSTING TORQUE: 339 Nm
- FASTENING TORQUE: 339 Nm
- IPM: 0 1,000 / 0 2,400 / 0 3,500 / 0 3,500
- RPM: 0 900 / 0 1,650 / 0 2,400 / 0 2,400
- DRIVE CONTROL: 4-Mode with Auto Shut-Off Mode & Bolt Removal Mode
- LENGTH: 124.5 mm
- WEIGHT: 1.1 kg (Tool Only)

• WARRANTY: 5 Years