

Milwaukee M18FMTIW2F12-0 - 18V Brushless Mid-Torque 1/2" (Friction Ring) Impact Wrench (Tool Only)



Product Description

The M18 FUEL™ 1/2" Mid-Torque Impact Wrench with Friction Ring delivers access in tight spaces, up to 881 Nm of nut-busting torque, and maximum power to weight ratio. This battery-powered impact wrench weighs only 1.58 kg, making it extremely versatile, capable of performing a wide variety of applications. A POWERSTATE™ Brushless Motor provides the power needed to quickly perform many tasks, such as removing large bolts or lug nuts. The MILWAUKEE® 1/2" Mid-Torque Impact Wrench with Friction Ring is only 152 mm in length, providing users access to stubborn fasteners where larger impact wrenches cannot fit without needing to disassemble components to reach bolts. Tri-LEDs that surround the anvil deliver the user brighter light with fewer shadows. 4-Mode DRIVE CONTROL offers enhanced precision with a range of pre-set RPM and IPM levels, selectable from a single button on the tool. By selecting Mode 4, Auto Shut-Off Mode applies no more than 48 Nm of torque for hand-tight fastening applications to prevent overtightening. Mode 4 also features Bolt Removal Mode, where the tool delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops. REDLINK™ PLUS Intelligence electronics make these controls possible while ensuring maximum performance, protecting the tool against overloads, over-heating, and over-discharge. The M18™ REDLITHIUM™-ION battery pack (not included) fits all M18™ tools, delivering more work per charge and more work over the life of the pack.

Features

- Friction ring ensures quick and easy socket changes
- POWERSTATE™ Brushless Motor delivers up to 881 Nm of nut-busting torque
- 4-Mode DRIVE CONTROL provides control over output speed and power
- Auto Shut-Off Mode prevents over tightening and increases productivity by applying no more than 48 Nm of torque
- Bolt Removal Mode delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- 152 mm in length for maximum access in tight spaces
- Tri-LEDs deliver high definition lighting to increase workspace visibility with less shadows
- Works in up to 69kV environments
- REDLINK™ PLUS Intelligence ensures maximum performance and protects from overloads, heating and over-discharge

Specifications

- PLATFORM: M18 FUEL™
- ANVIL TYPE: 1/2" Square with Friction Ring
- NUT BUSTING TORQUE: 881 Nm
- FASTENING TORQUE: 746 Nm
- IPM: 0 - 900 / 0 - 2,100 / 0 - 3,100 / 0 - 3,100
- RPM: 0 - 1,250 / 0 - 1,950 / 0 - 2,575 / 0 - 2,575
- DRIVE CONTROL: 4-Mode with Auto Shut-Off Mode & Bolt Removal Mode
- LENGTH: 152 mm
- WEIGHT: 1.58 kg (Tool Only)
- WARRANTY: 5 Years