

**Dewalt DCZ441P1X1T-XE** - 18V 54V 4 Piece Brushless Drill/Driver/Grinder/Wrench Combo Kit (1 x 5.0Ah / 1 x 9.0Ah)



# **Product Description**

# Kit Includes

- DCD999 18V XR XRP Hammer Drill Driver with Flexvolt Advantage
- DCF887 18V Brushless Impact Driver
- DCG418 54V XR Flexvolt 125mm Angle Grinder
- DCF899 18V 1/2" Drive Brushless Impact Wrench
- 1 x 18/54V Flexvolt 9.0Ah Battery
- 1 x 18V 5.0Ah Battery
- Fast Charger
- TSTAK Case
- Dewalt Bag

### DCD999 - 18V XR XRP Hammer Drill Driver with Flexvolt Advantage

- FLEXVOLT ADVANTANGE tool technology: the tool uses intelligent electornics to sense what battery is in the tool and increase power and torque when using FLEXVOLT batteries
- 51% more power when using DCB547 XR FLEXVOLT 9Ah battery compared with DCB184 18V XR 5Ah battery
- 42% more power when using DCB546 XR FLEXVOLT 6Ah battery compared with DCB184 18V XR 5Ah battery
- All metal chuck for improved grip on drilling and screwdriving accessories
- Electronic Clutch with 11 position adjustable torque control for optimised precision when screw driving
- Foot LED with delay feature for improved visibility and flashlight functionality
- Efficient intelligent trigger allowing total control over all applications
- Valigetta compatibile TSTAK
- Weight: 1.61 kg
- Max Drilling Capacity (wood): 55 mm
- Max Drilling Capacity (metal): 15 mm
- Max Drilling Capacity (masonry): 13 mm
- Max Torque (Hard): 126 Nm
- Max Torque (Soft): 67 Nm
- No Load Speed (Drilling / Driving Mode): 0-450/1300/2000 RPM
- No Load Speed (Hammer Mode): 0-500/1500/2250 rpm
- Beats per Minute: 38250 bpm
- Battery Voltage: 18
- Battery Chemistry:Li-Ion
- Power Output: 1296 W
- Chuck capacity: 1.5-13 mm
- No. of Speeds: 3
- Length: 213 mm
- Height: 208 mm
- Depth: 70 mm
- Sound Pressure: 94 dB(A)

- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 105 dB(A)
- Sound Power Uncertainty: 3 dB(A)
- Hand/Arm Vibration Drilling into metal: 2.7 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration Hammer drilling into concrete: 12.5 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- $\bullet\,$  Hand/Arm Vibration Screw driving without impact: <2.5  $m/s^2$
- Uncertainty K 3 (Vibration): 1.5 m/s<sup>2</sup>
- Includes
  - Magnetic Bit Holder
  - Side Handle
  - $\circ~$  Belt Hook
  - $\circ~$  TSTAK Compatible Box

### DCF887 - 18v Brushless Impact Driver

- High power Brushless motor outputting up to 205Nm of torque ensures heavy applications are completed quickly
- Application control is achieved through 3 motor speeds and torque settings including PrecisionDrive
- PrecisionDrive mode offers additional control in screwdriving applications to avoid material and fastener damage
- Super lightweight and compact the tool is very comfortable to use and fits in small spaces
- 3x LED "Halo" light ring offers excellent workpiece lighting
- 1/4" (6.35mm) 'drop in' bit holder allows for quick, one handed fitment
- Voltage: 18V
- No load speed:
  - Speed 1: 0-1000rpm
  - Speed 2: 0-2800rpm
  - Speed 3: 0-3250rpm
- Max torque: 205Nm
- Halo 3-Led lights
- Drop & load bit holder
- Weight:1.3kg

# DCG418 - 54V XR Flexvolt 125mm Angle Grinder

- 54V Brushless motor enables improved performance in demanding applications
- Electronic Brake stops the wheel quickly when the trigger is disengaged
- Electronic Clutch reduces the kickback reaction in the event of a pinch or stall
- A mesh cover over air intake vents restricts dust being sucked through the motor
- Rubber overmould provides enhanced grip and comfort
- 54V XR Flexvolt battery provides maximum power and performance
- Recessed spindle lock design allows max depth of cut and greater protection to button when using in confined spaces
- Two position side handle offers greater comfort and control
- Weight: 2.18kg
- Max Disc Diameter: 125mm
- Spindle Thread: M14
- No Load Speed 9000 RPM
- Switch Type: Trigger
- Power Source: Cordless
- Perform and Protect: true
- Brake: true
- Clutch: true
- Quick Change Flange: true
- Length: 400 mm
- Height: 125 mm
- Hand/Arm Vibration Grinding: 6.1 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration Sanding: 2.5 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- Sound Pressure: 84 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 95 m/s<sup>2</sup>
- Sound Power Uncertainty:3 dB(A)
- Includes
  - $\circ~$  2 position side handle
  - $\circ~$  Keyless protective guard
  - Blade wrench
  - $\circ~$  Battery and charger sold separately

### DCF899 - 18V 1/2" Drive Brushless Impact Wrench

- Latest generation 18V BRUSHLESS XR Li-Ion High Torque Wrench
- Powerful fan cooled motor delivers up to 950Nm of torque and 2400 impacts per minute for heavy duty fastening applications

- Up to 1625Nm of "breakaway" torque ensures removal of the tighest bolts
- 3 Speed and torque settings gives you the control to best suit your applciation
- 1/2"" (13 mm) square drive with detent pin allows for more efficient torque delivery and excellent socket retention
- Bright white LED with delay feature for improved visibility and flashlight functionality
- Comfortable rubber XR grip and switch for greater application comfort and maximum control
- Voltage: 18 V
- Bit Holder: 1/2" (12.7mm)
- Power Output: 610 Watts
- No Load Speed: 0 400 / 1200 /1900 rpm
- Impacts per Minute: 0 2400 ipm
- Max. Torque: 950 Nm
- Max. Bolt Diameter: M20
- Weight: 2.62 kg
- Length: 224 mm
- Height: 225 mm
- Hand/Arm Vibration Impact: 13 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 5.9 m/s<sup>2</sup>
- Sound Pressure: 101 dB(A)
- Uncertainty K 1 (Sound): 3 dB(A)
- Accoustic Pressure: 112 dB(A)
- Uncertainty K 2 (Sound): 3 dB(A)
- Battery chemistry: XR Li-Ion