

## Dewalt DCZ596X2T-XE - 18V/54V 5 Piece Brushless Combo Kit (2 x 9.0Ah)



### Product Description

---

#### Kit Includes

- DCD999 - 18V XR XRP Hammer Drill Driver with Flexvolt Advantage
- DCF887 - 18V Brushless Impact Driver
- DCG418 - 54V XR Flexvolt 125mm Angle Grinder
- DCS578 - 54V XR Flexvolt 184mm Circular Saw
- DCS389 - 54V XR Flexvolt Reciprocating Saw
- 1 x 18/54V Flexvolt 9.0Ah Battery
- 1 x 18V 5.0Ah Battery
- Fast Charger
- TSTAK Case
- Dewalt Bag

#### DCD999 - 18V XR XRP Hammer Drill Driver with Flexvolt Advantage

- FLEXVOLT ADVANTAGE tool technology: the tool uses intelligent electronics to sense what battery is in the tool and increase power and torque when using FLEXVOLT batteries
- 51% more power when using DCB547 XR FLEXVOLT 9Ah battery compared with DCB184 18V XR 5Ah battery
- 42% more power when using DCB546 XR FLEXVOLT 6Ah battery compared with DCB184 18V XR 5Ah battery
- All metal chuck for improved grip on drilling and screwdriving accessories
- Electronic Clutch with 11 position adjustable torque control for optimised precision when screw driving
- Foot LED with delay feature for improved visibility and flashlight functionality
- Efficient intelligent trigger allowing total control over all applications
- Valigetta compatibile TSTAK
- Weight: 1.61 kg
- Max Drilling Capacity (wood): 55 mm
- Max Drilling Capacity (metal): 15 mm
- Max Drilling Capacity (masonry): 13 mm
- Max Torque (Hard): 126 Nm
- Max Torque (Soft): 67 Nm
- No Load Speed (Drilling / Driving Mode): 0-450/1300/2000 RPM
- No Load Speed (Hammer Mode): 0-500/1500/2250 rpm
- Beats per Minute: 38250 bpm
- Battery Voltage: 18
- Battery Chemistry: Li-Ion
- Power Output: 1296 W
- Chuck capacity: 1.5-13 mm
- No. of Speeds: 3
- Length: 213 mm
- Height: 208 mm
- Depth: 70 mm
- Sound Pressure: 94 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)

- Sound Power: 105 dB(A)
- Sound Power Uncertainty: 3 dB(A)
- Hand/Arm Vibration - Drilling into metal: 2.7 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Hammer drilling into concrete: 12.5 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Screw driving without impact: <2.5 m/s<sup>2</sup>
- Uncertainty K 3 (Vibration): 1.5 m/s<sup>2</sup>
- Includes
  - Magnetic Bit Holder
  - Side Handle
  - Belt Hook
  - TSTAK Compatible Box

#### **DCF887 - 18v Brushless Impact Driver**

- High power Brushless motor outputting up to 205Nm of torque ensures heavy applications are completed quickly
- Application control is achieved through 3 motor speeds and torque settings including PrecisionDrive
- PrecisionDrive mode offers additional control in screwdriving applications to avoid material and fastener damage
- Super lightweight and compact the tool is very comfortable to use and fits in small spaces
- 3x LED "Halo" light ring offers excellent workpiece lighting
- 1/4" (6.35mm) 'drop in' bit holder allows for quick, one handed fitment
- Voltage: 18V
- No load speed:
  - Speed 1: 0-1000rpm
  - Speed 2: 0-2800rpm
  - Speed 3: 0-3250rpm
- Max torque: 205Nm
- Halo 3-Led lights
- Drop & load bit holder
- Weight:1.3kg

#### **DCG418 - 54V XR Flexvolt 125mm Angle Grinder**

- 54V Brushless motor enables improved performance in demanding applications
- Electronic Brake stops the wheel quickly when the trigger is disengaged
- Electronic Clutch reduces the kickback reaction in the event of a pinch or stall
- A mesh cover over air intake vents restricts dust being sucked through the motor
- Rubber overmould provides enhanced grip and comfort
- 54V XR Flexvolt battery provides maximum power and performance
- Recessed spindle lock design allows max depth of cut and greater protection to button when using in confined spaces
- Two position side handle offers greater comfort and control
- Weight: 2.18kg
- Max Disc Diameter: 125mm
- Spindle Thread: M14
- No Load Speed 9000 RPM
- Switch Type: Trigger
- Power Source: Cordless
- Perform and Protect: true
- Brake: true
- Clutch: true
- Quick Change Flange: true
- Length: 400 mm
- Height: 125 mm
- Hand/Arm Vibration - Grinding: 6.1 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Sanding: 2.5 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- Sound Pressure: 84 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 95 m/s<sup>2</sup>
- Sound Power Uncertainty: 3 dB(A)
- Includes
  - 2 position side handle
  - Keyless protective guard
  - Blade wrench
  - Battery and charger sold separately

#### **DCS578 - 54V XR Flexvolt 184mm Circular Saw**

- 54V FLEXVOLT system giving corded performance
- DEWALT Brushless Motor for power, extended run-time, reliability & durability
- General purpose ripping, crosscutting and bevelling circular saw for wood and other construction materials

- Variable adjustment of the bevel angle to 57 degrees
- Scale for precise cutting depth setting to 67 mm
- Optimum balance for safe, fatigue-free operation
- Stable block construction for low vibration running and long service life
- Additional handle for safe two-handed work
- Direct Airlock Compatibility allows quick, secure connection to extraction hose
- Dust blower keeps cut line clear of dust and debris
- LED work light for improved cut line visibility
- Weight: 3.6kg
- Bevel Capacity: 57°
- No Load Speed: 5800 RPM
- Blade Bore: 20mm
- Blade Diameter: 184mm
- Max Depth of Cut at 90°: 64mm
- Power Source: Cordless
- Length: 355 mm
- Height: 245 mm
- Hand/Arm Vibration: 2.2 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Sound Pressure: 90 dB(A)
- Sound Pressure Uncertainty: 3 dB(A)
- Sound Power: 101 dB(A)
- Sound Power Uncertainty: 3 dB(A)
- Includes
  - Rip fence
  - Precision 24 tooth saw blade
  - Blade Spanner
  - Dust Extraction Spout

#### **DCS389 - 54V XR Flexvolt Reciprocating Saw**

- 54V XR Flexvolt same power as corded
- Lever action keyless blade clamp for quick and easy blade changes
- Intelligent variable speed trigger, lock off switch and electronic motor brake for quick controlled cuts and enhanced work safety
- Two position blade clamp allows for flush cutting and increased versatility
- Pivoting adjustable shoe with open top for high stability and blade visibility during a cut
- Improved ergonomic design
- Crank type drive train that reduces vibration
- Tool free blade change lever
- LED light for cutline illumination
- Weight: 3.54kg
- Max Cutting Capacity (Steel Section and Pipes): 130mm
- Max Cutting Capacity (PVC): 160mm
- Max Cutting Capacity (wood): 300mm
- No Load Stroke Rate: 0-3000 SPM
- Length: 455mm
- Height: 175 mm
- Sound Pressure: 84 dB(A)
- Sound Pressure Uncertainty: 5 dB(A)
- Sound Power: 95 dB(A)
- Sound Power Uncertainty: 5 dB(A)
- Hand/Arm Vibration - Cutting boards: 15.3 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Cutting wooden beams: 15.9 m/s<sup>2</sup>
- Uncertainty K 3 (Vibration): 1.5 m/s<sup>2</sup>