

Makita DLX2412T - 18V 2 Piece Brushless Drill/Driver Combo Kit (2 x 5.0Ah)



Product Description

Includes

- DHP486Z 18V Brushless Hammer Driver Drill
- DTD154Z 18V Brushless 3-Stage Impact Driver
- 2 X BL1850B 5.0Ah Batteries
- DC18RC Single Port Rapid Charger
- Kitbox

DHP486Z - 18V Brushless Hammer Driver Drill

- Massive drilling capacity with 152mm hole saw and 50mm auger bit capacity
- High powered Brushless motor produces 141Nm peak torque
- Compact overall length only 178mm for use in narrow work spaces
- High durability aluminium gear housing
- \bullet Mechanical 2 speed gearing with all metal gear construction
- Impact Rate
 - o Hi: 0 31,500ipm
 - O Lo: 0 8,250ipm
- Max. drilling capacities in masonry: 16mm
- Max. drilling capacities in steel: 13mm
- Max. drilling capacities in wood
 - O Auger bit: 50mm
 - O Self-feeding bit: 76mm
 - O Hole saw: 152mm
- Max. lock torque: 125Nm
- Max. tightening torque
 - Hard: 130NmSoft: 65Nm
- No Load Speed
 - o Hi: 0 2,100rpm
 - o Lo: 0 550rpm
- Skin weight: 2.1kg
- Voltage: 18V
- Weight (with battery): 2.7kg
- Includes
 - o Grip assembly (127701-6)
 - o Depth rod (122576-8)
 - o Belt clip (346317-0, 251314-2)
 - o Bit holder (452947-8)
 - o + Bit (784637-8)

- Brushless motor for more power and longer runtimes
- Aluminium hammer case
- One touch bit installation
- Electronic 3 stage impact selection
- T:mode for self drilling screws
- Variable speed control by trigger
- Ergonomically designed handle
- Impact Rate 1st: 0-3,800ipm
- Impact Rate 2nd: 0-2,600ipm
- Impact Rate 3rd: 0-1,100ipm
- Max Fastening Torque: 175N.m
- Net Weight: 1.5kg w/BL1860B
- No Load Speed 1st: 0-3,600rpm
- No Load Speed 2nd: 0-2,100rpm
- No Load Speed 3rd: 0-1,100rpm
- No Loud Speed Std. 0 1,1001pt
- Overall Length: 117mm
- Specifications Capacity Coarse Thread: 22-125mm
- Specifications Capacity High Tensile Bolt: M5-M14
- Specifications Capacity Machine Screws: M4-M8
- Specifications Capacity Standard Bolt: M5-M16