

## Cabac T8229 - Digital Multimeter 5 In 1 Auto Range



## **Product Description**

5 in 1 Auto Range Digital Multimeter With Alarm

- CATIII 600V
- Sound & light warning for incorrect insertion of leads
- Temperature F° or C°
- Auto range / Manual range
- Data hold with backlight
- Maximum value measurement
- Auto power off
- Display: 3999 counts
- Continuity check with buzzer
- Diode test
- Rugged case with soft boot
- Compliance and Safety: IEC61010 1 CATII 1000V/CATIII 600V

Feature	Range	Accuracy
AC/DC Voltage	400m/4/40/400/1000V	±0.7% to 2%
AC/DC Current	400μ/4000μ/40m/400mA 10A	±1.2% to 3%
Resistance	400/4k/40k/400k/4M/4MΩ	±1.0%
Capacitance	40/400m/4/40μ/100μF	±3.0%
Frequency	10/100/1k/10k/100kHz	±2.0%
Duty Cycle	0.1% ~ 99.9%	±3.0%
Temperature	-20°C ~ 1000°C	±3.0% or ±2°C, 0°F
(thermocouple)	0°F ~ 1800°F	±3.0% or ±4°F
Temperature (NTC)	0°C ~ 40°C±2°C : 32°F ~ 104°F	±4°F
Humidity	20% ~ 95%RH	±5.0RH
Light	4000Lux/40000Lux	±5.0%
Sound level	40 ~ 100dB	±5dB

Continuity	$600\Omega$ , Threshold $50$ to $250\Omega$	Response < 100ms
------------	---	------------------

• Each unit is supplied in a gift box with test leads, thermocouple adaptor and manual

• Batteries: 3 x AA

• Size: H195mm x W92mm x T55mm

• Weight: Approx. 400g (including batteries)