

Husqvarna DE110i - 36V Dust Extractor (Tool Only)



Product Description

This versatile H-class dust extractor is powered by Husqvarna's own 36 V BLi batteries and is an excellent match for handheld battery equipment. It features a user-friendly HMI and an e-flow function that automatically adjusts the air flow while securing high runtime from the batteries. Its high water protection enables fast and efficient decontamination. It also features embedded connectivity allowing you to swiftly monitor location, service and filter status along with other valuable usage data.

Features

- Flexible battery power - Autonomy and flexibility are yours with this battery-powered dust extractor. Skip cords and don't worry about power source on the job site. Battery run time is optimised thanks to the ingenious e-flow system which automatically adjusts air flow.
- Safety focus - The dust extractor complies with the latest H-class standards for dust extractors for heavy-duty usage. It contains a HEPA filter (with EN1822 certification) which is separated from the pre-filter. An integrated filter alarm with adjustable hose-diameter indicates when it is time to clean the filter. Cleaning can be done by simply pressing a button.
- Easy to transport - Thanks to its compact size and light weight, the dust extractor is easy to transport. Smart details, such as lifting hooks, the possibility to attach hoses, wand and floor tool to the machine and the ability to drive it on its two wheels allow for smooth manoeuvring.
- Operate more sustainably with e-flow - While optimising the airspeed through the whole filter saturation process, e-flow technology reduces energy consumption up to 30%*. At the same time sound levels are reduced up to 8 dB(A)**. *) Based on an independently verified power consumption test, conducted in laboratory environment, measuring current at nominal voltage with e-flow activated, without any restrictions in the system. Power is calculated from the current/voltage and compared with the power consumption at full

flow, also without restrictions. **) Based on inhouse test conducted for models DE 110 and DE 120 in a laboratory environment, using the dust extractors without any restrictions in the system, measuring the noise level with and without e-flow activated.

- Easy to clean and maintain - The high water protection standard allows for easy cleaning and decontamination of the machine. The HMI gives warnings on operational maintenance for early and on-site trouble-shooting.
- Improved Longopac® attachment system - The easy-to-use, Longopac® attachment system and a V-shaped tray ensures easy mounting. Due to the special pleat-cover, no dust gathers in the folds.
- Optimised accessory range - The complete accessory range is further optimised for construction. A sturdy floor tool with large opening can handle even coarse dust. The wand, hoses and adapters with transport caps ensure smooth operation and transport. For even easier transport convenience, optional hose bags are available.

Specifications

- MOTOR
 - Output power: 0.9 kW
 - Power source: Battery
- BATTERY
 - Battery eco system: i-Series
- DIMENSIONS
 - Product size width: 400 mm
 - Product size height: 1,000 mm
 - Product size length: 670 mm
 - Weight: 26 kg