

Dewalt DW621-XE - Plunge Router 1100W C/W Dust Ext. Vs 8-24000RPM



Product Description

Features

- Precision micro-adjuster allows depth of cut adjustment accurate to 0.1 mm results
- Unique through the column dust extraction for excellent cutter visibility - no adaptor or hose which restrict visibility is required
- Power switch mounted in the handle for ease of use features lock off and lock on actions
- Full wave electronic speed control with feedback ensures the selected speed is maintained under any load for a consistent finish in all grades of timber, aluminium and plastics
- Soft start to eliminate any small initial movement that might misalign the cutter
- Two column precision guide with phosphor bronze bushing - the extra broad column provides superior rigidity for the greatest accuracy in this size of router
- Rubber coated handles provide a comfortable grip and their low down position aid control of the router
- 3 stage depth stop adjustment enables cuts of various depths to be made in one operation without time consuming setting up
- Spindle lock mechanism for quick and easy cutter changes with a single spanner

Specifications

- Power Input: 1100 Watts
- Power Output: 620 Watts
- No Load Speed: 8000-24000 rpm
- Plunge Stroke/Movement: 55 mm
- Collet Size: 6 - 12.7 mm
- Max. Cutter Diameter: 36 mm
- Weight: 3.1 kg
- Length: 165 mm
- Height: 325 mm
- Hand/Arm Vibration: 3.3 m/s²
- Uncertainty K 1 (Vibration): 1.5 m/s²
- Sound Pressure: 86 dB(A)
- Uncertainty K 1 (Sound): 3 dB(A)
- Acoustic Pressure: 95 dB(A)
- Uncertainty K 2 (Sound): 3 dB(A)

Includes

- Parallel fence with built-in micro adjustment
- Dust extraction adapter and cap
- 6mm & 12.7mm Collet
- 17/10 mm spanner