

## Dewalt DCH254M2-XE - 18V 3-Mode SDS+ Rotary Hammer Kit (2 x 4.0Ah)



### Product Description

---

#### Kit Includes

- DCH254 - Rotary Hammer
- 2 x 18V 4.0Ah batteries
- Charger
- Kitbox
- Multi-position side handle
- Quick release SDS-Plus toolholder
- Quick release 13mm 3 jaw chuck

#### Features

- Ideal for drilling anchors and fixing holes into concrete, brick and masonry from 4mm to 24mm
- Rotation stop mode for light chiselling in plaster, tiles and render and impact stop mode for rotary only drilling in wood and metal
- Quick release SDS-Plus toolholder and keyless chuck supplied for easy switching between hammer / rotary hammer and rotary only applications
- Best in class vibration, 6.6m/s<sup>2</sup> reduces user fatigue and maximises operating periods
- Bright white LED with delay feature improves visibility

#### Specifications

- Battery: XR Li-Ion
- Voltage: 18 V
- Power Output: 400 Watts
- No Load Speed: 0-1200 rpm
- Impact energy (EPTA 05/2009): 2.1 J
- Blows per Minute: 0-4500 bpm
- Tool Holder: SDS-Plus
- Max. Drilling Capacity [Wood]: 26 mm
- Max. Drilling Capacity [Metal]: 13 mm
- Max. Drilling Capacity [Concrete]: 24 mm
- Weight: 3.2 kg
- Length: 328 mm
- Height: 202 mm
- Width: 85 mm
- Hand/Arm Vibration: 6.6 m/s<sup>2</sup>
- Uncertainty K 1 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Chisel: 5.4 m/s<sup>2</sup>
- Uncertainty K 2 (Vibration): 1.5 m/s<sup>2</sup>
- Hand/Arm Vibration - Metal: 2.5 m/s<sup>2</sup>
- Uncertainty K 3 (Vibration): 1.5 m/s<sup>2</sup>
- Sound Pressure: 86 dB(A)
- Uncertainty K 1 (Sound): 3 dB(A)
- Acoustic Pressure: 97 dB(A)

- Uncertainty K 2 (Sound): 3 dB(A)