

Makita HR4013C - Rotary Hammer 1100W 2 Mode SDS Max 40mm Kitbox



Product Description

Features

- AVT (Anti-Vibation Technology)
- Vibration absorbing handle is completely separate from the motor housing to produce unrivalled low level of vibration
- Active Dynamic vibration absorber ensures operation with extremely low vibration
- Damper spring absorbs force caused by drill bit at the moment of impact
- Soft No Load reduces vibration of tool body when idling while also minimising deflection of the bit tip from aiming point when starting chipping
- Easy to operate operation mode change lever. Located on top of the motor housing for reduced possibility of breakage
- 11.4 joules of impact power
- Lock on switch for continuous chiseling applications
- Torque limiter
- Trigger switch for intermittent chiseling applications
- One touch sliding SDS Max type chuck
- Electronic with: Constant speed control and Soft Start for reducing start-up torque
- $\bullet\,$ LED power light that indicates trouble with the electric circuit
- $\bullet\,$ LED service light that indicates when to replace carbon brush
- Variable speed control by dial
- Soft grip provides more comfort and control

Specifications

Continuous rating input: 1,100WImpacts Per Minute: 1,450-2,900

• Joules: 11.4j

Max. capacity - Concrete: 40mmMax. core bit dia.: 105mm

• Net weight: 6.8kg

No load speed: 250-500rpmOverall length: 479mmPower supply cord: 5.0m

Includes

- Depth Gauge
- Side Handle (135269-8)
- Bit Grease 100mL (194683-7)